



Shop Order

2020 Metalfab Stock Pumper	
----------------------------	--

Sales Rep: Metalfab Ltd Drawing #: FT-11294 Est. Delivery Date: / / Customer PO #: Customer #: QPF #:	Terms: Chassis, Body and Equipment Net 30 Penalty: None
---	--

Quote No: 10009-0016
 Job/Order No: 21380
 05/07/2020

Page 1

PART NO	QTY	DESCRIPTION
	1	== Metalfab Pumper - ULC 05/13 - 0.000 ==
	1	CHANGE ORDER E
00-05-0010	1	Dealer - Metalfab
00-10-1500	1	Metalfab Pumper
00-20-0500	1	List of References not provided
00-20-1000	1	Company Profile
00-20-1500	1	Standard Body Warranty
00-20-1550	1	Metalfab Limited Ten (10) Year Paint and Corrosion Warranty
00-20-1600	1	Waterous Pump Warranty - 5 years
00-20-1800	1	Polypropylene Tank Lifetime Warranty
00-20-2000	1	Plant Visits - unlimited at customer expense
00-20-3000	1	No Bonding Required
00-20-3500	1	Certification for Fusion Welding of Aluminum
00-20-4000	1	Quality System registered to ISO 9001:2015
00-20-4500	1	Fire Apparatus Manufacturers' Association Membership
	1	GENERAL INFORMATION
10-11-0000	1	Intent E
10-11-0110	1	Vehicle data recorder included with chassis Includes seatbelt display mounted in overhead console.
10-11-1100	1	ULC S515-13 and NFPA 1901-2016 Compliance Include applicable NFPA warning labels.
10-11-1500	1	ULC Testing - Pumper - Imperial units of measure
10-11-2100	1	Maximum length not specified E
10-11-2200	1	Maximum height not specified E
10-11-2300	1	Overall length is less than 30'
10-11-2500	1	General Construction
10-11-3000	1	Manuals - two copies ***Two copies of manuals are required.
10-11-3500	1	Delivery - FOB Metalfab, Training at Metalfab
10-11-4300	1	Payment Terms - Chassis and Body NET 30
10-20-1000	1	Hose bed capacity - standard ULC Pumper
10-20-2000	1	Equipment carrying capacity - standard ULC Pumper

PART NO	QTY	DESCRIPTION
	1	CHASSIS INFORMATION
20-11-1000	1	Chassis - International HV607 four door 44,000lb GVWR 14000 lb front axle 30000lb rear axle 230" wheelbase 119" cab to axle Cummins L9 450 HP @ 2100rpm, 2200 governed rpm 1250 lb/ft @ 1400rpm Allison 3000 EVS - 5 speed 65MPH top speed 325 Amp Alternator 189L fuel tank, LH Amber LED marking lights Brake lights to activate with exhaust brake Color is 2303 Red
20-11-1500	1	2013 Emission chassis modifications
20-11-1700	1	Chassis Motor Vehicle Inspection required - NB E
20-21-0500	1	Fluid capacity plate
20-21-0600	1	Pumping test plate
20-21-1030	1	Maximum riders sign - 5 persons
20-21-1510	1	Seat belt warning labels - 4 door chassis
20-21-1560	1	LED Tire Pressure Indicators - Single Axle
20-21-1600	1	Apparatus Information Label An information label is provided in the chassis cab, visible to the driver, stating: "When manufactured, this vehicle was: ** m high ** m long ** kg GVW Changes in height since the apparatus was manufactured shall be noted on this plate by the Fire Department"
20-21-2000	1	Non removable key
20-21-2500	1	Shifter lock not required E
20-21-3500	1	Rear step warning label
20-21-3800	1	Front mudflaps
20-21-4000	1	Rear mudflaps - Metalfab Logo
20-31-0200	1	Fuel fill label -Ultra Low Sulfur Diesel only
20-31-1100	1	Alum tread fuel tank covers, diamond grip steps, Conv - 4 dr Deck and diamondback steps to be similar to Lambton Shore M18-19923 as discussed at pre-construction meeting of 03.02.2020
20-31-1510	1	Special compartments in chassis steps with light, door ajar Located on the right side. Compartment to be as large as possible
20-31-1900	1	Chassis cab painted single color by chassis OEM
20-31-4500	1	Price Adjustment
20-31-7000	1	SS nut covers, hub caps and high hats - single axle
20-31-7500	1	Console in cab Install siren (50-11-14AA), pump shift (30-51-0400), PTO hourmeter (70-21-2100) and radio provision (50-35-0500) for a customer installed Motorola XPR 5550 E in console. Storage area with hinged cover and lift and turn latch provided at rear of console. Gray zolatone finish There will storage for the following customer supplied accessories: Thermal Imager: MSA Evolution 5000 that measures 10" long x 5.5" wide Gas Monitor: MSA Altair 5 that measures 5" long x 3" wide Portable Radio Charger: Motorola XPR 7350E MSA G1 battery charger that measures 13.25" long x 5" wide As discussed at the pre-construction meeting of 03.02.2020 and confirmed by e-mail on 03.09.2020 Department will approve the final layout prior to the build.

PART NO	QTY	DESCRIPTION
20-41-0600	1	Intake air shutoff for engine not required
20-41-0900	1	Auxiliary braking system disabled when pumping
20-41-1100	1	Transmission programming - Allison WT
20-41-1500	1	Extend exhaust pipe - RS front of rear wheels E
		Engineering to specify exhaust pipe material as required by the chassis manufacturer.
		Engineering to sign off on the exhaust configuration to make sure it meets the chassis manufacturer's emission specifications.
20-41-1801	1	Battery boost terminals not required - batteries accessible
20-41-2000	1	Chassis batteries remain in OEM location
20-41-2510	1	Fuel fill at step fuel tank under cab
20-41-2600	1	Chassis fuel tank remains in OEM location
20-41-5000	1	Rear Tow Hooks - under body
		*** Flat bar tow hooks under rear step (2)
20-51-0700	1	Master Battery Disconnect included with chassis
20-51-2500	1	Back up alarm included with chassis
20-51-3400	1	Protection valve installed for air operated accessories
20-51-6200	3	120 volt 20 A shore line connection in chassis cab
		Standard 5-20R duplex receptacle in chassis cab, not fused. For battery conditioner to plug into.
		Receptacle to be min 12" off floor to meet ULC.
		2nd and 3rd Outlets to be installed on the back of the console (20-31-7500) as discussed at the pre-construction meeting of 03.02.2020 and confirmed by e-mail on 03.13.2020
20-51-6600	1	Kussmaul Pump Plus conditioner/compressor
		Conditioner located in cab and compressor located R1 compartment under the compartment depth change on the left side as approved by Todd Finnie by e-mail on 05.05.2020.
20-51-7102	1	Electric System Manager included with chassis - Diamond Logic
20-51-7500	1	Super Auto eject for 120 v - 20 A with sealed enclosure
		Located in LS cab step area. Standard finish
20-51-8510	1	Engine compartment light LED
		Switched with park brake
20-51-9100	1	Air horns on hood, lanyard controlled
		Air horns and shields installed by Metalfab. Lanyard and push button on dash included with the chassis.
20-52-3000	1	Chassis steering wheel lined up by others
20-60-0400	1	Chassis wheelbase does change - by chassis dealer prior to delivery to Metalfab
	1	PUMP AND PLUMBING
30-11-3002	1	Waterous CXVPA 1250 PTO driven pump - 1050 IGPM
30-15-0304	1	Plumbing - non manifold pump SM SS E
30-20-0501	1	Valves, controls - compartment mounted panel - HEAT style
30-20-1003	1	Elkhart valves specified
30-20-1620	1	Piping stainless steel - non manifold Pumper
30-20-1700	1	1-1/2" thread specifications - NPSH
30-20-1800	1	2-1/2" thread specifications - CSA
		The thread will be CSA as discussed at the pre-construction meeting of 03.02.2020
30-20-2000	1	Piping hydrostatic test
30-20-2510	1	Anodes in suction and discharge piping - non manifold pump
		Install one anode on discharge side of pump, one anode on suction side of pump - do not use teflon tape or thread sealant.
		Paint flange silver and mask brass anode before painting for visibility.
30-21-95AA	1	Elkhart electric tank to pump with control on panel, SS, 3"
		There will be a single electric control on the pump panel to control the 3" tank to pump valve that is plumbed to 4" piping.

PART NO	QTY	DESCRIPTION
30-22-0520	1	Tank Fill valve 2" SS
30-31-4020	1	Suction - 6" not gated each side SS non manifold pump 6" header
30-32-7550	1	Suction - 2-1/2" left side SS, bleeder, non manifold pump
30-40-2006	1	4" right discharge, plumbed 3", non manifold pump, SS, bleeder
30-41-2040	1	2-1/2" RS discharge SS, bleeder, non manifold pump
30-41-2540	2	2-1/2" LS discharge SS, bleeder, non manifold pump
30-43-1520	1	2-1/2" rear discharge SS, plumbed 2-1/2", bleeder *** In hose bed, right side
30-44-0720	2	1-1/2" speedlay (each) through the pumphouse SS, plumbed 2" Removable trays required The color(s) of the discharges are to be red and blue as requested by Todd Finnie by e-mail on 03.13.2020
30-44-1040	1	Price Adjustment
30-44-1041	1	Price Adjustment
30-51-0400	1	Price Adjustment
30-51-0700	1	Pump Gearbox mounted manual over ride for pump shift E
30-51-1500	1	Power shift PTO - Automatic transmission
30-51-1501	1	PTO driveshaft E
30-51-6640	1	Class One "TPG Plus" Governor/Throttle
30-51-7002	1	Suction side relief V/V, non manifold pump
30-51-7712	1	Trident Air Primer 3 barrel 1 location 1- Main pump on panel only as confirmed at the pre-construction meeting of 03.02.2020
30-51-7720	1	Additional air tank for air primer system An additional air tank is provided to improve air primer capacity.
30-51-8100	1	Heat exchanger included with chassis
30-52-1000	1	Master drain V/V, 12 port
30-52-2000	1	Price Adjustment
30-52-55AA	1	Price Adjustment
	1	WATER AND FOAM TANKS
40-11-2100	1	Polypropylene water tank (Imperial gallons)
40-11-2200	1	Water tank capacity certification (tank manufacturer)
40-11-5000	1	Tank capacity 1000 Imperial Gallons
40-12-4500	1	Price Adjustment
40-21-1000	1	4" tank to pump connection
40-22-0500	1	2" tank fill connection
40-23-0500	1	1" water level gauge connection
40-23-1000	1	Price Adjustment
40-30-0400	1	3" plug in sump box
40-30-1000	1	Water Fill Box front left corner
40-31-0400	1	Rear dump valve not requested E
40-31-6050	1	Rear fill not requested E
	1	ELECTRICAL
50-11-0450	1	Base electrical system - International Diamond Logic multiplex
50-11-0600	1	Warning Light Certification
50-11-0700	1	Low Voltage Electrical system test
50-11-0800	1	Low Voltage Electrical System Documents As required by ULC and NFPA standards
50-11-0900	1	Rocker switch panel with master warning switch ***Rocker switch assignments: MASTER -LIGHT BAR RED -LIGHT BAR CLEAR -FLASHING WARNING -LEFT SIDE SCENE -RIGHT SIDE SCENE

PART NO	QTY	DESCRIPTION
		-REAR SCENE
50-11-14AA	1	<i>Whelen Siren 295HFS2</i>
50-11-1620	1	<i>Siren speaker, 100 watt, in front bumper</i>
50-11-2600	1	<i>Siren to be accessible to driver and officer</i>
50-11-5002	1	<i>Whelen Freedom IV Duo lightbar</i> WECAD drawings required.
50-11-50AA	1	<i>Whelen Pioneer summit series</i> To be mounted below the Whelen Freedom IV Duo lightbar. WECAD drawings required.
50-11-6615	1	<i>Whelen TAM83 traffic advisor - surface mount</i> There will be a deck plate guard over the traffic advisor to protect the unit as requested by the customer and discussed at the accessories meeting of 03.19.2020
50-12-8500	1	<i>Front LED flashers (pr)-Whelen red LED 400 - RED LS/BUE RS</i> Include black bezel. The LS flasher will be red and the RS flasher will be blue as discussed at the pre-construction meeting of 03.02.2020
50-12-8600	1	<i>Rear LED flashers (pr)-Whelen red LED 400 RED LS/BUE RS</i> Include black bezel. The LS flasher will be red and the RS flasher will be blue as discussed at the pre-construction meeting of 03.02.2020
50-12-8620	1	<i>Rear LED flashers (pr)-Whelan red LED 900 RED RS/BUE LS</i> Include black bezel. The RS flasher will be red and the LS flasher will be blue as discussed at the pre-construction meeting of 03.02.2020
50-12-8700	1	<i>Front side inter lts (pr) - Whelen red LED 400</i> Include black bezel.
50-12-8800	1	<i>Body side inter lts (pr)-Whelen red LED 400</i> Include black bezel.
50-12-8820	1	<i>Body side inter lts (pr)-Whelan red LED 900 with integral flasher</i> Include black bezel.
50-21-30AA	1	<i>Price Adjustment</i>
50-21-5100	1	Compartment lighting - LED tube lights in each compartment (rollup doors)
50-21-5500	1	<i>Door Ajar warning light</i> Bilingual warning label in cab to read: "Do Not Move Apparatus when Light is on"
50-21-8001	1	<i>Step lights for body steps - 4" LED</i> Switched with park brake.
50-21-8201	1	<i>Step lights for chassis steps - LED</i> Switched with park brake.
50-21-83AA	1	<i>12" LED lumabar for rear step/platform lighting</i> Switched with park brake.
50-21-8600	1	LED clearance lts and reflectors
50-21-8605	1	<i>Cast products license plate holder</i>
50-21-8800	1	<i>LED intermediate turn signal/clearance/reflector length >30'</i>

PART NO	QTY	DESCRIPTION
50-22-0700	1	Whelen 64 LED tail/brake-turn-backup module (pr)
50-31-6021	1	Whelen scene lights - C9SL - Left Side Switched in cab and wired to shed.Include black bezel.
50-31-6022	1	Whelen scene lights - C9SL - Rear Switched in cab. These lights cannot be managed as they are required for rear scene lighting to meet ULC. Interlock w/reverse of transmission. Include black bezel.
50-31-6023	1	Whelen scene lights - C9SL - Right Side Switched in cab and wired to shed.Include black bezel.
50-31-6560	1	Ground lighting (LED Lumabar) - 4 door chassis Switched with park brake.
50-31-6570	1	Ground lighting (LED Lumabar) - side mount body Switched with park brake.
50-35-0500	1	Provision for customer installed mobile radio Metalfab will prepare the console (20-31-7500) for the customer installed radio Motorola XPR 5550E and provide 12-volt power leads. There will be a second 12-volt power lead installed under the rear SCBA seats for a customer installed repeater that measures 5-1/2" x 5-1/2" x 1-7/8" As discussed at the pre-construction meeting of 03.02.2020 and confirmed by e-mail on 03.13.2020
50-35-0560	2	VHF antenna with base - commercial chassis There will be two (2) antenna bases supplied and installed as discussed at the pre-construction meeting of 03.02.2020. The antennas will be shipped loose so the customer's radio installer can properly trim the antenna at time of installation. One (1) antenna will be run to the center console (20-31-7500) and the second antenna will be run to the rear SCBA seat for a customer installed repeater as discussed with Todd Finnie by phone on 03.13.2020
50-99-10AA	1	Hose bed cover lights - 40" lumabar
50-99-11AA	1	3Kw Inverter with three (3) dual outlets There will be a 3000 kw Motormaster inverter supplied and installed under the rear SCBA seats in the chassis cab. It will be installed in this location to keep the inverter as close to the chassis batteries as possible. It will power an outlet in the center console (20-31-7500), one (1) in the L1 compartment and one (1) in the R1 compartment as requested and approved by Todd Finnie by e-mail on 03.13.2020.
50-99-25AA	1	Lighting for walkway in center of hose bed
	1	BODY
60-10-1400	1	Single axle extruded aluminum body Front of the body to be painted red smooth aluminum. Full width hose bed.
60-10-141A	1	Ladder storage under tank - subframe - beam mounted type tube
60-10-4100	1	No "beavertail" rear step supports
60-10-4600	1	Smooth Painted fender surround
60-10-4700	1	Integral aluminum fender trim
60-10-5400	1	Diamondback pumphouse steps To be standard finish as discussed at the pre-construction meeting of 03.02.2020
60-10-5440	1	Diamondback 14" rear step To be standard finish as discussed at the pre-construction meeting of 03.02.2020
60-10-6500	1	Bolt on extruded aluminum rub rail E Red/ white DOT reflective in rubrail. ** No bolt on rub rail on front and rear of the pump panel.

PART NO	QTY	DESCRIPTION
60-11-0300	1	Front left side compartments full height E
60-11-0700	1	Front right side compartments full height E
60-11-1000	1	Rear left side compartments full height E
60-11-1400	1	Rear right side compartments full height E
60-11-2000	2	High side compartment (over 18") each
60-11-3200	1	Full Height Rear compartment
60-11-5500	2	Rollup door - standard height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5520	5	Rollup door - full height Natural aluminum finish Includes magnetic door switch, LED tube lights, rubber bumpers to prevent pinch point
60-11-5655	1	Amdor pull straps - L2, R2
60-11-5660	1	Amdor pull straps - L1, L3, R1, R3, B1
60-31-4100	1	Extruded aluminum handrails Minimum 2" clearance from handrail to any surface
60-31-5000	1	Zico access Ladder at rear of unit Minimum 7" clearance between rung and any obstruction
60-31-5600	1	Grab handles at front of body next to pump panel - as required Maximum height between steps is 18"
60-31-5800	1	Step on rear of body above rear compartment Diamond back stepping material, There will be delineation stripes to meet NFPA. Install above traffic bar (50-11-6615) in order to protect the bar when hose are deployed. As discussed at the pre-construction meeting of 03.02.2020
60-31-6500	1	Compartment matting-Plastic Interlocking tile
60-31-8006	4	BA bottle compt (ea)-fender well Retaining loops included Customer to specify make and model of cylinder to be stored Make - MSA Model - G1 carbon Fiber Diameter of cylinder - 7" diameter or 20" around Overall length of cylinder - 23" Photo of valve/cap (to ensure retaining loop will fit) located in F:/Data/Jacques/Current Projects/2020 Stock As measured at the pre-construction meeting of 03.02.2020
60-31-8210	1	Vertical tool board - mounted on pull out tray There will be a tool board mounted on the tray (60-31-8700) in the L1 compartment up to the depth change as discussed at the pre-construction meeting of 03.02.2020. It will have the standard peg board holes on the entire surface of the board.
60-31-8400	1	Price Adjustment
60-31-8400	2	Fixed vertical partition A full height partition in front left compartment at rear of pump controls to separate pump operator's panel from the rest of the compartment. A partition in the shallow portion of the R1 compartment beside the pump access door to match the proposal drawing.
60-31-8700	5	Sliding tray (ea) - 400 pound capacity with open/close latch Reflective stripe is applied on the exposed edge for visibility when the compartment door is open Location of trays to match proposal drawing: 1. L1 compartment floor 2. L3 compartment floor 3. B1 compartment floor 4. R3 compartment floor

PART NO	QTY	DESCRIPTION
		5. R1 compartment floor
60-31-8800	1	Price Adjustment
60-31-9000	1	Tip down tray - 30 degree, 250 pound capacity Reflective stripe is applied on the exposed edge for visibility when the compartment door is open There will be a Tip Down tray supplied and installed in the L2 compartment to match the proposal drawing.
60-31-9600	1	Price Adjustment
60-31-9600	9	Adjustable shelf (ea) Reflective stripe is applied on the exposed edge for visibility when the compartment door is open Location of adjustable shelves to match proposal drawing: 1. L1 - Shallow 2. L1 - Shallow 3. L3 - Full depth 4. L3 - Full depth 5. R1 - Shallow 6. R1 - Shallow 7. R3 - Full depth 8. R3 - Full depth 9. B1 - Full depth Tray depth changed as discussed at accessories meeting review of 03.19.2020
60-32-3500	1	One adjustable and two fixed hose divider Hand hold required in end
60-32-7500	1	Hose bed - aluminum Walkway in the center of the hosebed - 24" wide
60-33-0000	1	Paint exterior - Imron Elite *** Paint code and color red to match the cab
60-33-0200	1	Undercoat vehicle with KROWN rust protection
60-33-0600	1	Chassis wheels not painted - Aluminum wheels
60-33-1000	1	Paint pump and plumbing job colour
60-33-1600	1	Special paint compartment interior - gray zolatone E
60-33-2200	1	Lettering - 80 letters up to 3" tall - 3 colour Lettering to match drawing approved by dealer
60-33-3000	1	Reflective stripe - 4" white 50% of perimeter each side and rear, 25% of perimeter front
60-33-3310	1	Reflective stripe - red and yellow chevron at rear Minimum 50% of rear vertical surface. Chevron on front bumper not required where front bumper extension was deleted and confirmed by Todd Finnie by e-mail on 03.19.2020.
60-33-3600	1	Reflective stripe - inside entry doors 96 square inches minimum inside each cab and crew cab entry door
60-33-4600	1	Black end tarps for speedlays
60-33-5000	1	Aluminum cover over hose bed with end tarps - black E
60-40-5500	2	Suction hose tube (each) with door To hold two 10' suction hoses (80-11-5000) and two 10' pike poles (80-13-2500). Door ajar switches required.
60-40-9000	1	Tube mount for ladders - Under tank Will accommodate a 24' section ladder (80-14-0500), 14' roof ladder (80-14-5500). Include Velcro straps at the end.

PART NO	QTY	DESCRIPTION
60-41-1015	2	Pike Pole tube in suction hose tube
60-91-0900	1	Top mount Coffin compartment - over pump house Door ajar switch required. Drain holes w/plastic tubes to below frame, LED lighting and plastic interlocking tile flooring
60-99-15AA	1	Hose bed cover locks - Same as Georgina
60-99-35AA	1	Diamond back overlays on top walkway There will be four (4) footman loops and two (2) pieces of velcro supplied and installed on the side walls of the walkway at 10' from the front hose bed partition to keep two (2) suction hoses 80-18-0500 secured. As requested at the pre-construction meeting of 03.02.2020
60-99-40AA	1	Price Adjustment
	1	INSTRUMENTATION
70-11-0000	1	Warning Label on Pump Operator's Panel
70-11-0600	1	Linkage control in left front compartment HEAT style design
70-11-1500	1	Stainless steel instrument panels No gauge or visual display can be higher than 84" above the operator's standing position Midpoint of any control cannot be higher than 72" above the operator's standing position
70-11-3200	1	Colour coded tags - Imperial units The color of the speedlays 30-44-0720 will be red and blue as advised by Todd Finnie by e-mail on 03.13.2020
70-11-52AA	1	End door on LS coffin compartment There will be a door on the left side of the body for the coffin compartment (60-91-0900) and the door will be hinged vertically at the front as discussed at the pre-construction meeting of 03.02.2020
70-11-7500	1	Heat pan-aluminum
70-11-8000	1	Heater in pump compartment Switch on pump operator's panel.
70-20-15AA	1	Price Adjustment
70-20-2130	7	2-1/2" pressure gauge - dual face 0-400 Gauge to be no more than 6" from edge of the gauge to the center of the control.
70-20-2500	1	Primer control - Trident for main pump on pump panel
70-20-3100	1	Class One Governor Control Throttle can be no lower than 42" and no higher than 72" from operator's standing position.
70-20-3500	1	Electric water level gauge on pump panel, Class One
70-20-361A	1	Remote PS Tank 2 gauges on the right side and rear of body There will be a PS Tank 2 gauge installed on the right side of the unit and on the rear of the unit as discussed at the pre-construction meeting of 03.02.2020
70-20-6500	1	Test gauge panel Mount below the compound gauges for proper draining
70-20-7500	1	Heat exchanger control valve
70-21-1500	1	Price Adjustment
70-21-2100	1	PTO Hourmeter Located in cab console.
70-21-5500	1	Panel readout for Battery Conditioner Located in the LS cab step area.
	1	ACCESSORIES
80-11-5000	4	6" x 10' lightweight suction hose (ea) There will be four (4) suction hoses supplied and installed on the unit as advised by Todd Finnie by e-mail on 03.13.2020. Two (2) will be stored in the tubes 60-40-5500 and two (2) will be installed

PART NO	QTY	DESCRIPTION
		in the hose bed.
80-12-2500	1	6" barrel strainer
80-13-0500	1	Rubber mallet
80-13-2500	2	Pike pole, fibreglass handle - 10' long Tube mounted (60-41-1015)
80-14-0500	1	24' 2 section extension ladder PEL 24 Tube mounted (60-40-9000)
80-14-5500	1	14' aluminum roof ladder PRL-14 Tube mounted (60-40-9000)
80-14-8500	1	10' aluminum folding attic ladder FL-10 Located in hosebed walkway.
80-14-9000	1	Attic ladder bracket (Zico)
80-18-0500	4	SCBA bracket with strap - compt mount There will be four (4) SCBA brackets supplied and installed in the R2 compartment for customer supplied MSA G1 SCBA that measure 25.5" high x 14" wide x 10" deep. As requested at the pre-construction meeting of 03.02.2020.
80-18-0600	4	SCBA brkt w/strap - ZICO ULLH-EZO - crew cab mount